K9AG Neo2-Digital

BIOS Treiber Utility Handbuch

Das Produktbild kann sich vom aktuellen Produkt unterscheiden.
Es dient nur als Hinweis.

AM2+ Ready

Recommended DVI-D LCD Models

LCD	Model	LCD	Model
AOC	171SP	ViewSonic	VA1912wb
AOC	210V	PHILIPS	170X6
LG	L226WTQ	CMV	CT-937D
HKC	170S1	SAMSUNG	SyncMaster 250bw
PHILIPS	VP930b	ViewSonic	VP920b
ViewSonic	983A	PHILIPS	190Cb
SAMSUNG	SyncMaster 940bw	□□□	A91
PHILIPS	190CW	Benq	FP71G
MAG	T7D	EIZO	FlexScan L685

MSI Reminds you :
Because of the limitations of chipset, this MB does not support Win98/ME.

Übersicht CPU Tabelle

Features

Live Update Online — The MSI Live Update online is designed to automatically download and update the BIOS and driver when there's a new version online. It helps reduce the risk of getting the wrong file and minimize the trouble of searching the files from MSI website.

Dual Core Center
- Key components status hardware monitor.
- Monitor the Dual Core CPU each unit status.
- D.O.T. Technology up to 12% improvement.
- Optimize System status define.
- Auto speed up with system loading change.

Live Update 3 — Live Update 3 is a single utility software that automatically checks BIOS, driver and utility updates and installs for you , which can save your time for searching and lower the risk while updating.

Cool'n'Quiet — AMD Cool'n'Quiet™ technology that based on famous PowerNow™ technology just brings fresh air to hot-fighting desktop platform. Cool'n'Quiet technology can automatically adjust processor ratio to throttle CPU speed with four modes.

Specifications

HDMI READY

HDMI: High Definition Multimedia Interface

The HDMI interface can turn many video cables and audio cables into 1 easy cable. Combine the RGB/Compostive connectors or DVI connectors and include digital audio connectors become 1 simple connector cable. The HDMI interface needs HDCP decoder on both output side and input side, for example, HDMI on VGA/MB will have HDCP in it, and LCD TVs/ LCD monitors will also need the HDCP decoder, then user can really enjoy the HD contains up to 1920*1080 resolution.

CPU

• AMD® Athlon 64 X2, Athlon 64, and Sempron in the Socket AM2 package.
Please refer to CPU Support for compatible CPU; the above description is for reference only.

FSB

• HyperTransport supporting speed up to 1GHz (2000MT/s)

Chipset

• AMD® 690G and SB600 Chipset

Main Memory

• Supports dual channel DDR2 533/667/800
- 4 DDR2 DIMMs (240pin / 1.8V)
- Supports a maximum memory size up to 8GB.

Slots

• 1 PCI Express x16 slot
• 2 PCI Express x1 slots
• 3 PCI slots, support 3.3V/ 5V PCI bus Interface.

On-Board IDE

• One IDE port by AMD® SB600
- Supports Ultra DMA 66/100/133 mode
- Supports PIO, Bus Master operation mode
- Can connect up to two IDE devices

On-Board SATA

• 4 SATA II ports by AMD® SB600
- Supports storage and data transfers at up to 300 MB/s

RAID Function

- SATA II 1~4 supports RAID 0, 1 and 0+1 mode by AMD® SB600

MSI Reminds You...
• The RAID setup floppy disk is optional depending on the districts. You can download the files from the website to make the setup disk.

Audio

• Chipset integrated by Realtek® ALC888
- Flexible 8-channel audio with jack sensing
- Compliant with Azalia 1.0 Spec

LAN

• Supports 10/100/1000 Fast Ethernet by Realtek 8111B

IEEE1394

• Chipset integrated by VIA® VT6308P
- Transfer rate is up to 400Mbps

Internal I/O Connectors

- ATX 24-pin power connector
- ATX 4-pin 12V CPU power connector
- CPU / System FAN connectors
- Chassis intrusion switch connector
- Front panel audio connector
- Front panel connector
- Clear CMOS jumper
- 1 x CD-in connector
- 1 x SPDIF out connector (optional, for HDMI graphics card only)
- 1 x Serial port connector
- 1 x IEEE1394 connector support additional 1 port (optional)
- 3 x USB 2.0 connectors support additional 6 ports
- 1 x Floppy disk drive connector
- 4 x Serial ATA II connectors
- 1 x ATA133 connector

MSI Reminds You...
• The floppy disk cable will be optional.

Back Panel I/O Ports

- 1 x HDMI port
- 1 x DVI-D port
- 1 x PS/2 keyboard
- 1 x PS/2 mouse
- 1 x IEEE1394 Port (optional)
- 1 x 6 in 1 audio jack
- 4 x USB 2.0 ports
- 1 x RJ45 LAN jack
- 1 x Graphics Card port

Dimension

• 30.5cm(L) x 21.0cm(W) ATX Form Factor

Mounting

• 6 mounting holes.

Product Accessories

IDE Cable

SATA+Power Cable

MSI Reminds You...
• The accessories will probably be different according to the different selling areas of product models. For details of accessories, please refer to the descriptions on the product package.

Express Download
MSI gibt Benutzern eine schnelle und einfache Möglichkeit Dateien herunter zu laden

Suchen :
Bitte Produktname, Dateiname oder Schlüsselwort eingeben.

Aktuelle Seite : Startseite > Produkte > Mainboards

Impressum | Kontakt © 2007 MSI Technology GmbH. Alle Rechte sowie Änderungen und Irrtümer vorbehalten..